



NINGBO DAYE POWER MACHINERY CO.,LTD

Address: No.1, Xin Yang Road, Di Tang Street, Yuyao, Zhejiang, China

Tel: 0086-574-62836898 Fax: 0086-574-62835099

WeChat/Whatsapp: +86 - 180 5858 4090

E-mail: sales@dayeepower.cn

<https://www.dayeepower.cn>

The Dayee policy of continuous improvement means that specifications can be changed without prior notice, the real product may vary from the pictures shown on this catalogue

Catalogue 2026

DAVEE POWER[®]





www.dayeepower.cn



Ningbo DAYE Power Machinery Co.,Ltd was founded in 2004. At that time, we purchased a lawnmower factory in Shanghai, and we became the earliest and most professional mower-making factory in China. DAYE got ISO9001 in 2004. After more than 20 years, DAYE has accumulated abundant R&D, manufacturing, and sales experience. As our customers, DAYE gives you so many choices. First, we have two kinds of power engines: gasoline and electric. Second, we provide different sizes to you: 13", 16", 17", 18", 19", 20" and 21". So we have over 80 models for you to choose. All of our models have CE, GS, EMC, NOISE, EUROV certificate. DAYE promises to you that every machine you get from our factory is comply with requirements of the certificates. DAYE has established stable and reliable parts supplying chain system. DAYE keeps and improves ISO9001 quality system continuously, and ensures the products quality and in time delivery. After more than 20 years effort, DAYE has gathered many outstanding technicians in the field. DAYE is the leader in new products development and can successfully develop new products in very short period.

1. We are the earliest lawnmower factory in China
2. We are the most professional mower-making factory in China
3. We have more than 20 years experience in lawn mower, and have accumulated abundant manufacturing and sales experience.

C O N T E N T S

Gasoline Lawn Mower Comfort Pro Series - - - - -	1-6
Gasoline Lawn Mower Premium Plus Series - - - - -	6-12
Gasoline Engine Series - - - - -	13-15

Gasoline Lawnmowers

Comfort Pro Series


The DAYEE comfort pro range of petrol Lawnmowers are powered by DAYEE and B&S engines. This range of mowers are available in self-propelled models and vary in cutting widths from 410mm, 425mm, 460mm to 510mm. Selected models also feature both mulching and side discharge options.

The products in comfort pro range are equipped with ergonomic grips with self-propelled drive, quick fix and release handlebar with height adjustment, easy storage, filling level indicator, high wheel for easier traction, front handling panel for carrying and much more.





New



Self-drive System

Self-propelled for easily tackling larger jobs.

Powerful DAYEE Engine

Provides easy starting and low fuel consumption.

Handle Height Adjustment

3 positions allows handle height flexibility.

Large Collection Bag

Features a high airflow plastic top with a level indicator to ensure maximum grass pickup.

Central Cutting Height Adjustment

Quick and easy adjustment of the grass cutting height. One lever affects the whole deck.

3 in 1 Function

Provides rear collection, side discharge and mulching for different cutting options.

410/425/460/510MM Cutting Width

Durable steel deck is ideal for small to large lawns.

New

16"



Model	DY162-131PB-06	DY162-131SB-06	DY162-150PB-06
Cutting Width(Inch/mm)	16/410	16/410	16/410
Driving Type	Hand Push	Self-Propelled	Hand Push
Deck Material	Steel	Steel	Steel
Rated Speed(Rpm)	2800	2800	2800
Engine Model	Ducar DV130	Ducar DV130	Ducar DV150
Engine Displacement(CC)	131	131	150
Fuel Tank Capacity(L)	1.0	1.0	1.0
Oil Tank Capacity(L)	0.45	0.45	0.45
Lithium Battery Capacity	N/A	N/A	N/A
Cutting Height Adjustment	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central
Cutting Method	Rear Collection	Rear Collection	Rear Collection
Handle Height Adjustment	3 Positions	3 Positions	3 Positions
Grass Catcher Capacity(L)	50	50	50
Gear Box	N/A	China	N/A
Front /Rear Wheel Size(Inch)	6" / 8"	6" / 8"	6" / 8"
Carton Size(mm)	720*520*440	720*520*440	720*520*440
Loading Qty(20'/40'/40HQ)(Pcs)	175/355/426	175/355/426	175/355/426

New

16"/17"



Model	DY162-150SB-06	DY162-125SB-06	DY171-150PB-06
Cutting Width(Inch/mm)	16/410	16/410	17/425
Driving Type	Self-Propelled	Self-Propelled	Hand Push
Deck Material	Steel	Steel	Steel
Rated Speed(Rpm)	2800	2800	2800
Engine Model	Ducar DV150	B&S300E Series	Ducar DV150
Engine Displacement(CC)	150	125	150
Fuel Tank Capacity(L)	1.0	0.8	1.0
Oil Tank Capacity(L)	0.45	0.47	0.45
Lithium Battery Capacity	N/A	N/A	N/A
Cutting Height Adjustment	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central
Cutting Method	Rear Collection	Rear Collection	Rear Collection
Handle Height Adjustment	3 Positions	3 Positions	3 Positions
Grass Catcher Capacity(L)	50	50	50
Gear Box	China	China	N/A
Front /Rear Wheel Size(Inch)	6" / 8"	6" / 8"	7" / 10"
Carton Size(mm)	720*520*440	720*520*440	740*515*440
Loading Qty(20'/40'/40HQ)(Pcs)	175/355/426	175/355/426	170/355/426



New
17"

Model	DY171-150SB-06	DY171-150SM-06	DY171-125SM-06
Cutting Width(Inch/mm)	17/425	17/425	17/425
Driving Type	Self-Propelled	Self-Propelled	Self-Propelled
Deck Material	Steel	Steel	Steel
Rated Speed(Rpm)	2800	2800	2800
Engine Model	Ducar DV150	Ducar DV150	B&S 450E Series
Engine Displacement(CC)	150	150	125
Fuel Tank Capacity(L)	1.0	1.0	0.8
Oil Tank Capacity(L)	0.45	0.45	0.47
Lithum Battery Capacity	N/A	N/A	N/A
Cutting Height Adjustment	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central
Cutting Method	Rear Collection	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)
Handle Height Adjustment	3 Positions	3 Positions	3 Positions
Grass Catcher Capacity(L)	50	50	50
Gear Box	China	China	China
Front /Rear Wheel Size(Inch)	7" / 10"	7" / 10"	7" / 10"
Carton Size(mm)	740*515*440	740*515*440	740*515*440
Loading Qty(20'/40'/40HQ)(Pcs)	170/355/426	170/355/426	170/355/426



New
17"/18"

Model	DY171-150SM-06E	DY181-150PB-06	DY181-150SB-06
Cutting Width(Inch/mm)	17/425	18/460	18/460
Driving Type	Self-Propelled	Hand Push	Self-Propelled
Deck Material	Steel	Steel	Steel
Rated Speed(Rpm)	2800	2800	2800
Engine Model	Ducar DV150E, Electric Start	Ducar DV150	Ducar DV150
Engine Displacement(CC)	150	150	150
Fuel Tank Capacity(L)	1.0	1.0	1.0
Oil Tank Capacity(L)	0.45	0.45	0.45
Lithum Battery Capacity	18V/2.0Ah	N/A	N/A
Cutting Height Adjustment	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central
Cutting Method	3 in 1(Rear Collection,Mulching, Side Discharge)	Rear Collection	Rear Collection
Handle Height Adjustment	3 Positions	3 Positions	3 Positions
Grass Catcher Capacity(L)	50	60	60
Gear Box	China	N/A	China
Front /Rear Wheel Size(Inch)	7" / 10"	7" / 10"	7" / 10"
Carton Size(mm)	740*515*475	785*570*460	785*570*460
Loading Qty(20'/40'/40HQ)(Pcs)	136/284/355	140/300/300	140/300/300

New

18"



Electric Start

Model	DY181-150SM-06	DY181-125SM-06	DY181-150SM-06E
Cutting Width(Inch/mm)	18/460	18/460	18/460
Driving Type	Self-Propelled	Self-Propelled	Self-Propelled
Deck Material	Steel	Steel	Steel
Rated Speed(Rpm)	2800	2800	2800
Engine Model	Ducar DV150	B&S 450E Series	Ducar DV150E, Electric Start
Engine Displacement(CC)	150	125	150
Fuel Tank Capacity(L)	1.0	0.8	1.0
Oil Tank Capacity(L)	0.45	0.47	0.45
Lithum Battery Capacity	N/A	N/A	18V/2.0Ah
Cutting Height Adjustment	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central
Cutting Method	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)
Handle Height Adjustment	3 Positions	3 Positions	3 Positions
Grass Catcher Capacity(L)	60	60	60
Gear Box	China	China	China
Front /Rear Wheel Size(Inch)	7" / 10"	7" / 10"	7" / 10"
Carton Size(mm)	785*570*460	785*570*460	785*570*500
Loading Qty(20'/40'/40HQ)(Pcs)	140/300/300	140/300/300	112/240/300

New

20"



Electric Start

Model	DY201-173SM-06	DY201-173SM-06E	DY201-196SM-06
Cutting Width(Inch/mm)	20/510	20/510	20/510
Driving Type	Self-Propelled	Self-Propelled	Self-Propelled
Deck Material	Steel	Steel	Steel
Rated Speed(Rpm)	2800	2800	2800
Engine Model	DY1P70FA	DY1P70FAD, Electric Start	DY1P70FB
Engine Displacement(CC)	173	173	196
Fuel Tank Capacity(L)	1.5	1.5	1.5
Oil Tank Capacity(L)	0.6	0.6	0.6
Lithum Battery Capacity	N/A	N/A	N/A
Cutting Height Adjustment	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central
Cutting Method	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)
Handle Height Adjustment	3 Positions	3 Positions	3 Positions
Grass Catcher Capacity(L)	60	60	60
Gear Box	China	China	N/A
Front /Rear Wheel Size(Inch)	7" / 10"	7" / 10"	7" / 10"
Carton Size(mm)	830*570*475	830*570*525	830*570*475
Loading Qty(20'/40'/40HQ)(Pcs)	112/224/280	112/224/280	112/224/280



Electric Start



New

20"

Model	DY201-196SM-06E	DY201-161SM-06
Cutting Width(Inch/mm)	20/510	20/510
Driving Type	Self-Propelled	Self-Propelled
Deck Material	Steel	Steel
Rated Speed(Rpm)	2800	2800
Engine Model	DY1P70FBD, Electric Start	B&S DOV750EX Series
Engine Displacement(CC)	196	161
Fuel Tank Capacity(L)	1.5	1.0
Oil Tank Capacity(L)	0.6	0.6
Lithum Battery Capacity	18V/2.0Ah	N/A
Cutting Height Adjustment	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central
Cutting Method	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)
Handle Height Adjustment	3 Positions	3 Positions
Grass Catcher Capacity(L)	60	60
Gear Box	China	China
Front /Rear Wheel Size(Inch)	7" / 10"	7" / 10"
Carton Size(mm)	830*570*525	830*570*475
Loading Qty(20'/40'/40HQ)(Pcs)	112/224/280	112/224/280



Gasoline Lawnmowers

Premium Plus Series

The DAYEE premium plus range of petrol Lawnmowers are powered by DAYEE ,B&S and Honda engines. Featuring rich and high specification. This range of mowers are available in self-propelled models and vary in cutting widths from 460mm ,510mm to 530mm. Selected models also feature both mulching and side discharge options.

The products in premium plus range are equipped with ergonomic grips with panel , self-propelled drive, variable speed drive, lithium electric start , quick fix and release handlebar with height adjustment, easy storage, filling level indicator, high wheel for easier traction ,front handling panel for carrying and much more.





New

Self-drive System

Self-propelled for easily tackling larger jobs.

Electric Start

Equipped with lithium-start engine by 18V/2.0Ah battery for easy start and operation.

Easy Foldable Handle Bar

Easily fold the handle to minimize space required for storing and transportation.

Powerful DAYEE Engine

Provides easy starting and low fuel consumption.

Variable Speed

Variable speed drive system gives you total control of your mowing speed.

Large Collection Bag

Features a high airflow plastic top with a level indicator to ensure maximum grass pickup.

Handle Height Adjustment

3 positions allows handle height flexibility.

Central Cutting Height Adjustment

Quick and easy adjustment of the grass cutting height. One lever affects the whole deck.

3 in 1 Function

Provides rear collection, side discharge and mulching for different cutting options.

460/510/530MM Cutting Width

Durable steel deck is ideal for medium to large lawns.



New

18"



Electric Start

Model	DY182-150SM-06	DY182-150SM-06V	DY182-150SM-06E
Cutting Width(Inch/mm)	18/460	18/460	18/460
Rated Speed(Rpm)	2800	2800	2800
Engine Model	Ducar DV150	Ducar DV150	Ducar DV150E,Electric Start
Engine Displacement(CC)	150	150	150
Fuel Tank Cacacity(L)	1.0	1.0	1.0
Oil Tank Cacacity(L)	0.45	0.45	0.45
Lithum Battery Capacity	N/A	N/A	18V/2.0Ah
Cutting Height Adjustment	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central
Driving Type	Self-Propelled	Self-Propelled,Variable Speed	Self-Propelled
Deck Material	Steel	Steel	Steel
Cutting Method	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)
Handle Height Adjustment	3 Positions	3 Positions	3 Positions
Grass Catcher Capacity(L)	60L	60L	60L
Gear Box	China	GT	China
Front /Rear Wheel Size(Inch)	8" / 11"	8" / 11"	8" / 11"
Carton Size(mm)	830*570*500	830*570*500	830*570*500
Loading Qty(20'/40'/40HQ)(Pcs)	112/224/280	112/224/280	112/224/280

New

18"



Electric Start
Variable Speed

Model	DY182-150SM-06VE	DY182-140SM-06	DY182-145SM-06
Cutting Width(Inch/mm)	18/460	18/460	18/460
Rated Speed(Rpm)	2800	2800	2800
Engine Model	Ducar DV150E,Electric Start	B&S500E Series	Honda GCV145
Engine Displacement(CC)	150	140	145
Fuel Tank Cacacity(L)	1.0	0.8	0.91
Oil Tank Cacacity(L)	0.45	0.47	0.4
Lithum Battery Capacity	18V/2.0Ah	N/A	N/A
Cutting Height Adjustment	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central
Driving Type	Self-Propelled,Variable Speed	Self-Propelled	Self-Propelled
Deck Material	Steel	Steel	Steel
Cutting Method	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)
Handle Height Adjustment	3 Positions	3 Positions	3 Positions
Grass Catcher Capacity(L)	60L	60L	60L
Gear Box	GT	China	China
Front /Rear Wheel Size(Inch)	8" / 11"	8" / 11"	8" / 11"
Carton Size(mm)	830*570*500	830*570*500	830*570*500
Loading Qty(20'/40'/40HQ)(Pcs)	112/224/280	112/224/280	112/224/280



Model	DY202-173SM-06	DY202-173SM-06V	DY202-173SM-06E
Cutting Width(Inch/mm)	20/510	20/510	20/510
Rated Speed(Rpm)	2800	2800	2800
Engine Model	DY1P70FA	DY1P70FA	DY1P70FAD,Electric Start
Engine Displacement(CC)	173	173	173
Fuel Tank Cacacity(L)	1.5	1.5	1.5
Oil Tank Cacacity(L)	0.6	0.6	0.6
Lithum Battery Capacity	N/A	N/A	18V/2.0Ah
Cutting Height Adjustment	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central
Driving Type	Self-Propelled	Self-Propelled,Variable Speed	Self-Propelled
Deck Material	Steel	Steel	Steel
Cutting Method	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)
Handle Height Adjustment	3 Positions	3 Positions	3 Positions
Grass Catcher Capacity(L)	60L	60L	60L
Gear Box	China	GT	China
Front /Rear Wheel Size(Inch)	8" / 11"	8" / 11"	8" / 11"
Carton Size(mm)	890*570*500	890*570*500	890*570*500
Loading Qty(20'/40'/40HQ)(Pcs)	96/208/260	96/208/260	96/208/260



Model	DY202-173SM-06VE	DY202-196SM-06	DY202-196SM-06V
Cutting Width(Inch/mm)	20/510	20/510	20/510
Rated Speed(Rpm)	2800	2800	2800
Engine Model	DY1P70FAD,Electric Start	DY1P70FB	DY1P70FB
Engine Displacement(CC)	173	196	196
Fuel Tank Cacacity(L)	1.5	1.5	1.5
Oil Tank Cacacity(L)	0.6	0.6	0.6
Lithum Battery Capacity	18V/2.0Ah	N/A	N/A
Cutting Height Adjustment	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central
Driving Type	Self-Propelled,Variable Speed	Self-Propelled	Self-Propelled,Variable Speed
Deck Material	Steel	Steel	Steel
Cutting Method	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)
Handle Height Adjustment	3 Positions	3 Positions	3 Positions
Grass Catcher Capacity(L)	60L	60L	60L
Gear Box	GT	China	GT
Front /Rear Wheel Size(Inch)	8" / 11"	8" / 11"	8" / 11"
Carton Size(mm)	890*570*500	890*570*500	890*570*500
Loading Qty(20'/40'/40HQ)(Pcs)	96/208/260	96/208/260	96/208/260

New
20"



Model	DY202-196SM-06E	DY202-196SM-06VE	DY202-161SM-06
Cutting Width(Inch/mm)	20/510	20/510	20/510
Rated Speed(Rpm)	2800	2800	2800
Engine Model	DY1P70FBD,Electric Start	DY1P70FBD,Electric Start	B&S DOV 750EX
Engine Displacement(CC)	196	196	161
Fuel Tank Cacacity(L)	1.5	1.5	1
Oil Tank Cacacity(L)	0.6	0.6	0.6
Lithum Battery Capacity	18V/2.0Ah	18V/2.0Ah	N/A
Cutting Height Adjustment	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central
Driving Type	Self-Propelled	Self-Propelled,Variable Speed	Self-Propelled
Deck Material	Steel	Steel	Steel
Cutting Method	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)
Handle Height Adjustment	3 Positions	3 Positions	3 Positions
Grass Catcher Capacity(L)	60L	60L	60L
Gear Box	China	GT	China
Front /Rear Wheel Size(Inch)	8" / 11"	8" / 11"	8" / 11"
Carton Size(mm)	890*570*500	890*570*500	890*570*500
Loading Qty(20"/40"/40HQ)(Pcs)	96/208/260	96/208/260	96/208/260

New
20"/21"



Model	DY202-167SM-06	DY212-196SM-06	DY212-196SM-06V
Cutting Width(Inch/mm)	20/510	21/530	21/530
Rated Speed(Rpm)	2800	2800	2800
Engine Model	Honda GCV170	DY1P70FB	DY1P70FB
Engine Displacement(CC)	167	196	196
Fuel Tank Cacacity(L)	0.91	1.5	1.5
Oil Tank Cacacity(L)	0.4	0.6	0.6
Lithum Battery Capacity	N/A	N/A	N/A
Cutting Height Adjustment	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central
Driving Type	Self-Propelled	Self-Propelled	Self-Propelled,Variable Speed
Deck Material	Steel	Steel	Steel
Cutting Method	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)
Handle Height Adjustment	3 Positions	3 Positions	3 Positions
Grass Catcher Capacity(L)	60L	65L	65L
Gear Box	China	China	GT
Front /Rear Wheel Size(Inch)	8" / 11"	8" / 11"	8" / 11"
Carton Size(mm)	890*570*500	920*570*500	920*570*500
Loading Qty(20"/40"/40HQ)(Pcs)	96/208/260	96/200/250	96/200/250



Electric Start



Electric Start
Variable Speed

New
21"

Model	DY212-196SM-06E	DY212-196SM-06VE
Cutting Width(Inch/mm)	21/530	21/530
Rated Speed(Rpm)	2800	2800
Engine Model	DY1P70FBD,Electric Start	DY1P70FBD,Electric Start
Engine Displacement(CC)	196	196
Fuel Tank Cacacity(L)	1.5	1.5
Oil Tank Cacacity(L)	0.6	0.6
Lithum Battery Capacity	18V/2.0Ah	18V/2.0Ah
Cutting Height Adjustment	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central
Driving Type	Self-Propelled	Self-Propelled,Variable Speed
Deck Material	Steel	Steel
Cutting Method	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)
Handle Height Adjustment	3 Positions	3 Positions
Grass Catcher Capacity(L)	65L	65L
Gear Box	China	GT
Front /Rear Wheel Size(Inch)	8" / 11"	8" / 11"
Carton Size(mm)	920*570*500	920*570*500
Loading Qty(20'/40'/40HQ)(Pcs)	96/200/250	96/200/250



New
21"

Model	DY212-161SM-06	DY212-202SM-06
Cutting Width(Inch/mm)	21/530	21/530
Rated Speed(Rpm)	2800	2800
Engine Model	B&S DOV750EX	GCV200
Engine Displacement(CC)	161	202
Fuel Tank Cacacity(L)	1	0.91
Oil Tank Cacacity(L)	0.6	0.4
Lithum Battery Capacity	N/A	N/A
Cutting Height Adjustment	25-75mm,8 Positions,Central	25-75mm,8 Positions,Central
Driving Type	Self-Propelled	Self-Propelled
Deck Material	Steel	Steel
Cutting Method	3 in 1(Rear Collection,Mulching, Side Discharge)	3 in 1(Rear Collection,Mulching, Side Discharge)
Handle Height Adjustment	3 Positions	3 Positions
Grass Catcher Capacity(L)	65L	65L
Gear Box	China	China
Front /Rear Wheel Size(Inch)	8" / 11"	8" / 11"
Carton Size(mm)	920*570*500	920*570*500
Loading Qty(20'/40'/40HQ)(Pcs)	96/200/250	96/200/250

DAYEE Engine Series

POWERED BY **DUCAR**
POWER WITH VISION



Model No	DV130	DV150	DV170
Engine Type	Single cylinder, 4-stroke, air cooled,OHV	Single cylinder, 4-stroke, air cooled,OHV	Single cylinder, 4-stroke, air cooled,OHV
Displacement(cc)	131	150	173
BorexStore(mm)	61*45	65*45	70*45
Max Power(kW)@3600RPM	2.4	2.6	3.0
Electric Start System	NO	NO	NO
Fuel Tank Capacity(L)	1.0	1.0	1.0
Oil Tank Capacity(L)	0.45	0.45	0.45
Dimensions(mm)	328x308x245	328x308x245	328x308x245
N.W(kg)	7.6±0.5	7.7±0.5	7.7±0.5

DAYEE Engine Series

POWERED BY **DUCAR**
POWER WITH VISION



Model No	DV150E	DV170E
Engine Type	Single cylinder, 4-stroke, air cooled,OHV	Single cylinder, 4-stroke, air cooled,OHV
Displacement(cc)	150	173
BorexStore(mm)	61*45	70*45
Max Power(kW)@3600RPM	2.6	3.0
Electric Start System	Yes	Yes
Fuel Tank Capacity(L)	1.0	1.0
Oil Tank Capacity(L)	0.45	0.45
Dimensions(mm)	328x308x245	328x308x245
N.W(kg)	9.3±0.5	9.3±0.5

DAYEE Engine Series

POWERED BY **DAYEE**



Model No	DVIP65FC	DY1P70FA	DY1P70FB
Engine Type	Single cylinder, 4-stroke, air cooled,OHV	Single cylinder, 4-stroke, air cooled,OHV	Single cylinder, 4-stroke, air cooled,OHV
Displacement(cc)	161	173	196
BorexStore(mm)	65*48.5	70*45	70*51
Max Power(kW)@3600RPM	2.8	3.1	3.5
Electric Start System	NO	NO	NO
Fuel Tank Capacity(L)	1.3	1.5	1.5
Oil Tank Capacity(L)	0.6	0.6	0.6
Dimensions(mm)	390x360x360	430x350x360	430x350x360
N.W(kg)	10.7	13.5	13.6

DAYEE Engine Series

 POWERED BY



Model No	DY1P70FAD	DY1P70FBD
Engine Type	Single cylinder, 4-stroke, air cooled, OHV	Single cylinder, 4-stroke, air cooled, OHV
Displacement(cc)	173	196
Bore×Store(mm)	70*45	70*51
Max Power(kW)@3600RPM	3.1	3.5
Electric Start System	Yes	Yes
Fuel Tank Capacity(L)	1.5	1.5
Oil Tank Capacity(L)	0.6	0.6
Dimensions(mm)	430×350×360	430×350×360
N.W(kg)	15.3	15.4

B&S Engine Series


Model No	B&S 300E-Series™	B&S 450E-Series™
Engine Type	Single cylinder, 4-stroke, air cooled, OHV	Single cylinder, 4-stroke, air cooled, OHV
Displacement(cc)	125	125
Bore×Store(mm)	60*44.5	60*44.5
Max Power(kW)@3600RPM	1.66	1.66
Electric Start System	NO	NO
Fuel Tank Capacity(L)	0.8	0.8
Oil Tank Capacity(L)	0.47	0.47
Dimensions(mm)	347×310×244	347×310×244
N.W(kg)	7.7	7.7

B&S Engine Series


Model No	B&S 500E-Series™	B&S 750EX-Series™DOV
Engine Type	Single cylinder, 4-stroke, air cooled, OHV	Single cylinder, 4-stroke, air cooled, OHV
Displacement(cc)	140	161
Bore×Store(mm)	63.4*44.5	64*50
Max Power(kW)@3600RPM	1.66	2.58
Electric Start System	NO	NO
Fuel Tank Capacity(L)	0.8	1.0
Oil Tank Capacity(L)	0.47	0.6
Dimensions(mm)	347×310×244	369×325×254
N.W(kg)	8.2	11.1



HONDA
Engine Series
POWERED BY
HONDA



Model No	GCV145 Series	GCV170 Series	GCV200 Series
Engine Type	Single-Cylinder with aircooled, 4 stroke, OHV	Single-Cylinder with aircooled, 4 stroke, OHV	Single-Cylinder with aircooled, 4 stroke, OHV
Displacement(cc)	145	167	202
BorexStore(mm)	56*59	60*59	66*59
Max Power(kW)@3600RPM	3.1	3.6	4.2
Electric Start System	NO	NO	NO
Fuel Tank Capacity(L)	0.91	0.91	0.91
Oil Tank Capacity(L)	0.4	0.4	0.4
Dimensions(mm)	415 x 330 x 359	415 x 330 x 359	415 x 330 x 359
N.W(kg)	10.1	10.1	10.1